Paxton

Connecting a Avutec Gatekeeper ANPR camera to Net2

Overview

The Avutec Gatekeeper is an all-in-one license plate camera, including embedded software, analyzer and IR illuminator. With a range of action of 2 to 8 meters, the advanced camera ensures a smooth recognition of vehicles.

The ANPR reader has two cable inputs. One connects to the reader terminal of the Net2 plus and the other has an RJ45 connector which may be used to connect the camera to a PC LAN port to view the camera output and other settings. The camera needs to be configured to use the Wiegand output. A PC connection with the camera is not required during normal use.

The camera has a built in Wiegand interface to connect it to a Net2 plus doorcontroller. The Avutec Gatekeeper needs to be connected through Wiegand to the ACU using the wiring diagram below.

Cable Pinout	ACU terminal			
-	+12V	10	Red 12V dc	
-	Red LED	IØ	Red LED	
-	Amber LED	IØ	Amber LED	
-	Green LED		Green LED	Reader
D0	Wiegand D0		Data/D0	der 1
D1	Wiegand D1	IØ	Clock/D1	
-	NOT USED	IØ	Media Detect	
GND	0V	IØ	0V out	
	1	-		

Ensure any unused wires are safely terminated.

The camera needs to be powered by a Power over Ethernet + (POE+ 802.3at). It cannot be connected to the reader output terminals of the Net2 controller.

The ANPR integration in Net2 currently utilizes ASCII with a limitation of 11 characters. Some regions such as the US, Germany, & Benelux utilize special characters such as dashes & umlauts that are not currently supported.

In Net2 you need to set the following settings on the doorcontroller:

The reader type in Net2 should be set to: ANPR 26 bit Wiegand reader. The token data format in Net2 should be set to : ANPR 26 bit Wiegand.

For correct placement and installation of the Avutec Gatekeeper please follow the Avutec Gatekeeper installation guide.



- **L** +44 (0)1273 811011 support@paxton.co.uk
- S paxton.support
 - **(** +32 (0)78485147
- support@paxton-benelux.com S paxton.benelux.support
- **L** +1(800) 672-7298 supportUS@paxton-access.com
- S usapaxton.support

support@paxtonaccess.ae

S paxton.support





- - S paxton.soporte

L +44 (0)1273 811011

S paxton.support

support@paxton.co.uk

(+49 (0) 251 2080 6900

S paxton.gmbh.support

support@paxton-gmbh.de

- **(** +31 (0)76 3333 999 **(** +27 (0)21 4276691 support@paxton-benelux.com support@paxtonaccess.co.za S paxton.benelux.support S paxton.support **L** +11 5715088198 **L** +1 (864) 751-3501 ۹ soporte@paxton-access.com soporte@paxton-access.com S paxton.soporte
 - 2

(+33 (0)157 329356

S paxton.support

support@paxtonaccess.fr