

Paxton10 - Slimline reader

Paxton10

Overview

Continuing Paxton's long-standing tradition, offering a wide variety of reader types to suit all applications, the Slimline Reader has been designed to blend seamlessly into any interior style whilst offering ultimate installation simplicity via its 5m/ 16ft encapsulated cable.

The Slimline Reader, in its low profile compact package still provides all the functions you would expect from a Paxton10 reader. It supports all leading token types, including HID Prox®, MIFARE®, Paxton and EM, as well as offering Bluetooth for communication with long range or handsfree credentials and mobile telephones via the Paxton app.

Features

- Multi-format reading technology offering compatibility with Paxton, MIFARE®, HID Prox®, EM and more
- Low power sleep mode with capacitive wake-up
- Built in Bluetooth Low Energy support to allow communication to mobile and wearable devices
- Simple 2-part construction with encapsulated 5m/16ft cable
- IP67 rated
- Simple 4 wire installation





Token compatibility

Paxton		
Frequency		125kHz
Data read		Serial number (CSN) & User memory
Cloning resistance		Medium
EM4100/02		
Frequency		125kHz
Data read		Serial number (CSN)
Cloning resistance		Low
MIFARE®		
Frequency		13.56MHz
Data read		UID
Cloning resistance		Low



Electrical

Power consumption	1W	(Max)
Operating voltage	12V	
Current Draw	40mA	(Quiescent)
	100mA	(Max)



Communication

RFID frequency	125kHz & 13.56MHz	
Data connection	RS485/Paxton10 protocol	
Bluetooth®	2.4 GHz	
Token Mode	Up to 2cm	
Touch to Enter	Up to 1.5m	
Long Range	Up to 10m	



Hardware

Dimensions (W x H x D)	49mm x 104mm x 17.2mm	
Cable Type	22AWG, 4 core twisted pair	
Cable Length	5m	
Maximum cable extension length (Controller > Reader)	100m	
Sound	Piezo Buzzer	
Colour	Black	
Housing material	PC+ABS	
Warranty	Paxton 5 year	



Environment

Operating temperature	-35°C - +66°C
IP Rating	IP67
Mounting	Surface only, suitable for mounting on metal



Accessories and Sales codes

010-296	Paxton10 - Slimline reader
---------	----------------------------

