


## Overview

The wireless connector enables the award winning PaxLock Pro to connect to the Paxton10 system. The wireless connector communicates to the PaxLock Pro via Bluetooth®, and is designed for discreet ceiling or wall mounting.

## Features

- BLE connectivity
- Easy plug and play operation
- Health and fault finding LED's for visual diagnostics





### System

Maximum PaxLock Pros per connector	10
Number of cascaded connectors per controller	3



### Electrical

Power consumption	300mA (Max)
Operating voltage	Powered by RS485, 30VDC



### Communication

Maximum dataline connection - Controller to Connector	100m/328ft
Maximum dataline connection -Connector to Connector	100m/328ft
Data connection	RS485/Paxton10 protocol
Wireless	Bluetooth® 2.4GHz
Typical Wireless Range (to Paxlock)	15m/50ft



### Hardware

Dimensions (W x H x D)	164mm x 163mm x 34mm 6 29/64" x 6 27/64" x 1 11/32"
LED's	Green LED - Health, comms Blue LED - Bluetooth®
Warranty	Paxton 5 year



### Environment

Operating temperature	+32°F - +113°F
IP Rating	N/A if used outside, this unit must be mounted in a suitable housing
Mounting	Surface only / Backbox mounted

Certifications: UL 60950-1, FCC 15C