Paxton10 Wireless Connector

Overview

The wireless connector enables the award winning PaxLock Pro to connect to the Paxton10 system. The wireless connector communicates to the PaxLock Pro via Bluetooth®, and is designed for discreet ceiling or wall mounting.

Features

- BLE connectivity
- Easy plug and play operation
- Health and fault finding LED's for visual diagnostics



TDS-0014-AE

Specifications

Paxton10

System

Maximum PaxLock Pros per connector	10
Number of cascaded connectors per controller	3

Electrical

Power consumption	300mA (Max)
Operating voltage	Powered by RS485, 30VDC

Communication

Maximum dataline connection - Controller to Connector	100m
Maximum dataline connection -Connector to Connector	100m
Data connection	RS485/Paxton10 protocol
Wireless	Bluetooth® 2.4GHz
Typical Wireless Range (to Paxlock)	15m

Hardware

LED's	Green LED - Health, comms
	Blue LED - Bluetooth®
Warranty	Paxton 5 year

Environment

Operating temperature	0°C - +45°C
IP Rating	N/A - If used outside, this unit must be mounted in a suitable housing
Mounting	Surface only / Backbox mounted

Accessories and Sales codes

010-687-EX	Paxton10 - Wireless Connector

Dimensions



© Paxton Ltd 1.0.9