

PaxLock Pro2 Installation and Commissioning guide

Overview

When installing a PaxLock Pro2 it is important to ensure the environment the PaxLock Pro2 is to be installed in is fit for purpose.

This application note covers the preparation that should be carried out before, during and after installation to ensure the longevity of the PaxLock Pro2 as well as correct installation.

This application note also covers a few common problems which may impact the performance and quality of the PaxLock Pro2.

Checks to make prior to installation

Before installing the PaxLock Pro2 onto the door it is important to check that the door, frame and relevant door furniture are in good working order. This is important to ensure both the longevity and smooth operation of the PaxLock Pro2 once installed.

Through door holes

The PaxLock Pro2 has been designed to work with locksets that are either European (DIN 18251-1) or Scandinavian profile as shown in Figure 1.

The through door holes must be **9mm** diameter and the central follower must have at least **18mm** clearance around it.




Figure 1 - European drilling holes (Left) & Scandinavian drilling holes (Right)

Lockset

The PaxLock Pro2 should be installed with a new lockset to ensure smooth operation, as well as a key override to ensure access can be gained in the rare event of a unit failure.

The lockset must meet the following specifications:

- DIN 18251-1 certified for European locksets
- Backset of $\geq 55\text{mm}$
- Centres measurement of $\geq 70\text{mm}$ if using key override for European style locksets
- Centres measurement of $\geq 105\text{mm}$ if using key override for Scandinavian style locksets
- Turning angle of $\leq 45^\circ$

The lockset must be both horizontally and vertically aligned to the door as shown in Figure 2.

The use of the lockset with key override is recommended to ensure access can be gained in the power loss event of a unit failure.




Figure 2 - Correct installation of a lockset

Door Frame

It is best practice to ensure there is a gap of $\leq 3\text{mm}$ from the door edge to the frame. This is to ensure that if an anticord plunger is present on the Lock case, it can function correctly.

The door keep should also be $\leq 15\text{mm}$ to avoid clashing with the PaxLock Pro2 when the door is closed.




Figure 3 - 3mm gap from door frame to door edge.

Door usage

The PaxLock Pro2 is recommended for use on doors being operated up to 75 times per day. For usage above this number we would recommend a Paxton hard wired solution.

Floor

The distance between the bottom of the door and the floor must be sufficient to allow the door to freely open and close without rubbing on the floor.




Door Closer

If a door closer is being used it must be adjusted to ensure the door closes without slamming but does not require excessive force to open.

Door Stop

The use of a door stop is advised on doors that can hit an adjacent wall when fully opened. This will prevent damage being caused to the PaxLock Pro2.



Acoustic and draft seals

Should a door have either an acoustic or draft seal around the outer edge it is important that the door can still easily close without putting undue stress on the latch and strike plate. If this is not the case the strike plate may need adjusting.

Metal doors

The PaxLock Pro2 is suitable for installation onto metal doors providing both the width and lockset are within the specifications outlined on the PaxLock Pro2 datasheet. To ensure correct operation the following must be checked:

- If using in online mode, the Net2Air bridge or Paxton10 Wireless Connector may have to be positioned well within the 15m of range as a metal door will reduce the range of communication. To ensure reliable operation, standalone mode may be more appropriate.

Door Widths

Out of the box the PaxLock Pro2 will work with 35mm - 62mm door widths.

Cover plates

If a slimline electronic door handle is being replaced with the PaxLock Pro2, cover plates are available to cover any unused holes in the door. The cover plates can be fitted over the top of the PaxLock Pro2 and secured with 4 supplied wood screws; one in each corner. The appropriate cover plate will need to be ordered depending on whether a key override is present and matched to the centre measurement of the lockset.

Important note: Cover plates are provided for aesthetic purposes only and do not contribute to fire resistance
Also see: Cover plates dimensional drawing < <https://paxton.info/3560> >

BS EN179 – Emergency Exit devices for use on escape routes

BS EN179 is a standard for devices to be used in emergency situations where people are familiar with the emergency exit and its hardware, therefore a panic situation is unlikely to develop. This means lever handle operated escape mortice locks or push pads may be used.

The PaxLock Pro2 is certified to the BS EN179 standard meaning the product is suitable for use on emergency exits in areas where a panic situation is unlikely to develop. The PaxLock Pro2 must be used with the PaxLock Pro2 - Euro, EN179 kit or the door system will not be compliant to BS EN179.

Sales Code: 901-018 PaxLock Pro2 - Euro, EN179 kit

You can view the PaxLock Pro2's BS EN179 certification at the following links <https://paxton.info/10312> , <https://paxton.info/10313>

Fire Doors


The PaxLock Pro2 is compliant to EN 1634-1 covering both FD30 and FD60 rated timber fire doors. All door furniture used in the installation must have equivalent fire certification in order to comply. This includes the use of interdens as recommended by the lockset manufacturer.

During installation

EN179 Kit

The Union HD72 lock case is designed so that the front and rear of the lock case work independently of each other, allowing for single action egress. For this reason, a split spindle must be used with the lock case. The split spindle may need to be cut down, depending on the door width, there are marks on the split spindle to aid in cutting it down.

Note: When cutting down the split spindle we recommend a hack saw with 24 TPI (teeth per inch)




It is important to note that when installing the Union HD72 lock case the screws on the follower must always be located on the inside of door as this denotes the direction of escape. If they need to be moved over to the other side of the lock case, they must be removed and replaced one at a time.


Note: If both screws are removed at the same time you will be unable to screw them back in

PaxLock Pro2 Installation

The supplied template < <https://paxton.info/9932> > should be used to check that the holes in the door are in the right location and correctly sized for the PaxLock Pro2. To ensure the PaxLock Pro2 is perpendicular to the door edge it is important to mark and drill a 6mm hole for the anti rotation pin in the correct location, as indicated below.



When passing the PaxLock Pro2 through the door to fit it, the unit must sit completely flush against the face of the door. If this is not the case the holes in the door may need adjusting.



Post installation commissioning

Once the PaxLock Pro2 has been installed there are several checks that can be made to ensure the PaxLock Pro2 has been installed and is functioning correctly. When the PaxLock Pro2 is first powered up it will remain in an unlocked state. This will give you the chance to check the following;

1. Does the latch fully retract when depressing the handle?
2. Does the door open smoothly without rubbing on the frame, latch or floor?
3. When letting go of the handle does the latch fully return to its natural position?

4. Is it smooth and easy to open the door?
5. When closing the door does the latch sit within the keep?
6. When the door is closed does the deadbolt (if present) project smoothly into the keep?

If the answer is yes to all the above, then the unit can be bound to a Net2 or Paxton10 system, or a standalone pack can be enrolled. If the answer is no, refer to the troubleshooting guide below.

Replacing the Batteries

To replace the batteries of the PaxLock Pro2:

1. Carefully insert a small flat head screwdriver into the slot at the top of the battery side fascia and angle downwards to pop off the fascia
2. Open the battery case lid
3. Replace the 4 AA batteries inside and close the battery case lid
4. Place the rear fascia back over the handle and secure to the chassis, inserting at the bottom first and then the top, until you hear a click

Troubleshooting

To help improve the quality of the installation and the longevity of the product several common issues and potential solutions are listed below.

Problem	Recommendation
Lockset	
Lock case is old, worn or not freely moving	The lockset must be replaced.
The latch bolt is not fully retracting when the handle is fully depressed?	The turning angle of the lock case must be 45° or lower for the PaxLock Pro2 to fully retract the latch. If it is over this, the Lock case will need replacing.
When the door is closed the latch does not sit in the keep	The position of the keep and strike plate should be adjusted so that the latch sits comfortably in the keep when the door is closed. Failure to do this compromises the security of the door.
The lock cases will not retract the latch when the door is closed, even from the secure side of the door.	Remove the PaxLock from the door and independently check the operation of the lockset
PaxLock Pro2	
The edge of the PaxLock Pro2 or handle is clipping the door frame when opening and closing the door.	If this occurs, it may be a result of the backset on the lock case being too low. We recommend a minimum measurement of 55mm to be suitable for most doors. The Lock case will need replacing with one with an increased backset measurement if this is the case.
The PaxLock Pro2 will not sit flush against the door when fitting.	The through door holes must be 9mm diameter and the central follower must have at least 18mm clearance around it. If this is not the case it will need correcting before installing the PaxLock Pro2.
The PaxLock Pro2 is not responding when I present a token	Check the through door cable is fitted correctly to the battery side of the PaxLock Pro2. Try with a different token to see if the issue persists.
There is free play in the handles.	It is important the grub screws on both handles are fully tightened to remove any free play.

Door Furniture	
The door rubs against the frame/floor when opened.	The door or frame may need shaving down to ensure smooth operation.
The door is hitting the wall when opened.	It is important that a door stop is installed to prevent the handle hitting a wall or object when the door is opened fully. Failure to do this can damage the PaxLock Pro2 when swung open.
Door seals installed post install are applying too much pressure to the latch and deadbolt.	Door seals must be routed into the frame to prevent excessive force on the latch when the door is closed. The keep and strike plate may need to be moved if seals have been fitted without routing.
Net2	
Event in Net2: "Handle held down during operation"	This occurs when the handle of the PaxLock Pro2 is held down when a token is presented to the reader. To correctly use the PaxLock Pro2 present your token, wait for green LED & beep, then depress the handle
Event in Net2: "Secure-side handle stuck" or "Unsecure-side handle stuck"	These events indicate the respective PaxLock Pro2 handle has been held down for more than 30 seconds. Most likely someone holding the handle down for too long or something has been hung or left on the handle
Paxton10	
Event in Paxton10: "Secure-side handle stuck" or "Unsecure-side handle stuck"	These events indicate the respective PaxLock Pro2 handle has been held down for more than 30 seconds. Most likely someone holding the handle down for too long or something has been hung or left on the handle