Solo

Paxton Solo - Controller

Overview

The Solo - Controller is a compact, simple access controller designed for a quick and easy installation.

The Solo - Controller can be purchased with a 12V DC PSU with either a 1A or 2A supply. PCB only options are also available.



Features

- No network connection required
- No physical connection between controller and DoorTag
- Power options: 12V DC 1A or 2A
- Plastic enclosure options
- 5-year warranty



TDS-1092-ZA

Paxton

Specifications

Electrical

Operating Voltage	12-24V
Power Consumption	12Vdc Idle 21.95mA
	12Vdc Active 62.72mA
	24Vdc Idle 19mA
	24Vdc Active 40.8mA
Backup Battery	12V DC, 7Ah (Optional)
Relay rating	30V DC / 10A
Alarm output Current	1A

Communication

Bluetooth	BLE

Hardware

Door contact input	Yes
Exit button input	Push to make
Relays	1
Maximum number of DoorTags per door	4
Warranty	5 Years

Environment

Operating temperature	
150-020-ZA	0°C - 50°C
150-030-ZA	0°C - 40°C
150-040-ZA	0°C - 50°C
150-050-ZA	0°C - 50°C
IP Rating	N/A
Mounting	Wall

Accessories and Sales codes

150-020-ZA – Solo – Controller, with plastic housing

150-030-ZA – Solo – Controller, 12V 1A PSU, with plastic housing

150-040-ZA – Solo – Controller, PCB only

150-050-ZA – Solo – Controller, 12V 2A PSU, with plastic cabinet

Dimensions

150-020, 150-030



150-040



150-050



© Paxton Ltd Rev A